



AEROSPACE




**Drallim Industries Limited**  +44 (0)1424 205140  
Millwood House, Drury Lane,  
Ponswood Industrial Estate,  
St. Leonards on Sea,  +44 (0)1424 202140  
 email@drallim.com  
East Sussex. TN38 9BA, UK  www.drallim.com

An ISO 9001:2008 Approved Company  
Registered Office: Registered in England No 606278

## ***Floor Pan Fittings***

***The Drallim Group***  
*Leading innovators in technology and quality*

- This new range of floor pan fittings are light-weight, yet extremely strong and simple to fit and operate. Interiors can be changed from cargo carrying to passenger carrying duties in just a few minutes.
- The units incorporate a stud onto which a standard jaw fitting can be located, and a swivelling ring for use with cargo tie-down devices or webbing based lashings.
- Environmental protection is achieved using quality cadmium plating (alternative finishes available on request).
- The fittings are manufactured in the UK in our Aerospace approved manufacturing plant using the latest state of the art techniques.



### High Quality Specifications

Manufactured to the highest standards, defence standard cadmium plating for maximum endurance. Full material traceability as standard.

### Reduced Noise Cargo Ring

Where fitted, lashings can be fixed or tied on to the swivelling ring if required. The Cargo Ring folds away into the recess of the floor fitting when not in use for additional safety. The design features a silencer which effectively reduces noise caused by vibration.

### Strength Tested

Each manufactured batch is load tested to guarantee safe, quantifiable performance.

### Minimum Specification-Ring and Stud Fitting

■ Part No:	123CA16			
	RING		STUD	
	Vertical pull	45° Pull	Vertical pull	54° Pull
■ Proof Load (lbf):	2250	1875	3750	2909
■ Ultimate Design Load (lbf):	3000	2500	5000	5230
■ Weight:	0.38lbs/0.172kg			
■ NSN Number:	1680-99-820-8601			

A stud fitting without a ring can also be supplied.  
Various pan hole configurations are available.